

WRC924SC

90cm Stainless steel canopy hood with 720m3/h extraction, Hob2Hood, LED lighting, 3 fan speeds and touch controls.

RRP AUS \$899.00



## **Product Details**

| FEATURES  |   |   |  |
|---|---|---|--|
| Hob2Hood  | Powerful 720m3/hr extraction rate   | LED lighting  | 3 speed fan + Boost mode   |
| Auto off timer  | Dishwasher safe mesh filters  | Clean filter indicator  |  |
| BENEFITS  |   |   |  |
| seamlessly with your in<br>cooking smells and stea<br>rangehood will automati   | ogy, compatible rangehoods work<br>duction cooktop to clear your kitchen of<br>am. As you start cooking, the<br>cally turn on then intuitively adjust the<br>o match your cooking. How's that for |   | oowerful extraction rates ensuring your<br>king odours, vapours and excess heat in |
| Low energy, long lasting LED<br>With low energy use and a high illumination performance,<br>long-lasting LED lights make it easy to keep an eye on your<br>delicious cooking. |   | Easy clean touch contr<br>A flat touch control par<br>your rangehood even e | nel makes the most touched surface on  |
| micro-mesh filters can s<br>dishwasher or hand was  | nce, our easily removed aluminium<br>simply be washed safely in your<br>hed. Keep your rangehood looking great  |   |  |

and performing well with next to no effort.

# **Specifications**

## PRODUCT PROFILE

| Domestic warranty details<br>(yrs) | 2                   |
|------------------------------------|---------------------|
| Type of Rangehood                  | wall mounted canopy |
| Nominal width                      | 900                 |
| Finish of Rangehood                | stainless steel     |
|                                    |                     |

#### MOTOR/FAN

| Number of fans        | 1           |
|-----------------------|-------------|
| Number of fans speeds | 3           |
| Auto off              | Yes         |
| Type of motor         | centrifugal |
| Perimeter extraction  | No          |
| Maximum airflow M3/Hr | 720         |
| Noise level dB high   | 69          |
| Noise level dB low    | 52          |

### DIMENSIONS

| Total product height (mm) | 1180 |
|---------------------------|------|
| Total product width (mm)  | 900  |
| Total product depth (mm)  | 450  |
| Diameter of ducting (mm)  | 150  |

### CONTROLS

| Control panel              | electronic touch                                   |
|----------------------------|--|
| Safety/ display indicators | automatic safety cut<br>off,clean filter indicator |
| LED speed display          | Yes  |
| Hob2Hood function          | Yes  |



## WRC924SC

#### DIMENSIONS

| Minimum installation height<br>from cooking surface Gas<br>(mm)      | 650  |
|--|------|
| Minimum installation height<br>from cooking surface<br>Electric (mm) | 600  |
| Maximum canopy chimney<br>height (mm)                                | 1180 |
| Flue cover depth (mm)  | 290  |

#### FILTERS

| Number of filters | 3  |
|-------------------|--|
| Type of filter    | multilayer aluminum<br>micromesh filters |
| Dishwasher safe   | Yes                                      |

#### LIGHTS

| Number of lights | 2   |
|------------------|-----|
| Wattage of light | 5   |
| Type of light    | LED |

### **DUCTING / RECIRCULATION**

| optional accessory |
|--------------------|
| top                |
| Yes                |
|                    |

#### SHIPPING

| Shipping Weight (Kg)           | 18.23 |
|--------------------------------|-------|
| Pack Dimensions Height<br>(mm) | 630   |
| Pack Dimension Width<br>(mm)   | 980   |



### DUCTING / RECIRCULATION

| Recirculation kit                   | optional accessory |
|-------------------------------------|--------------------|
| Front recirculating option          | No                 |
| Ducting accessory<br>available      | MCFB33             |
| Type of filter                      | Charcoal           |
| Filter                              | Optional           |
| Number of optional filters required | two                |
| Ducting diameter (mm)               | 150                |

### SHIPPING

| Pack Dimension Depth | 465 |
|----------------------|-----|
| (mm)                 |     |



## **Terms and Conditions**

#### IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

#### **PRODUCT INFORMATION**

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous productdevelopment, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes theproducts that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products PtyLtd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours ofproducts illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

#### WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

#### ELECTROLUX HOME PRODUCTS AUSTRALIA

telephone: 1300 363 640 fax: 1800 350 067 email: customercare@electrolux.com.au web: www.electrolux.com.au

#### ELECTROLUX HOME PRODUCTS NEW ZEALAND telephone: 09 573 2230 fax: 09 573 2221 email: customercare@electrolux.co.nz web: www.electrolux.co.nz