RF 135mm f/1.8L IS USM

TECHNICAL SPECIFICATIONS





RF 135mm f/1.8L IS USM

Portrait shooting with a telephoto perspective



HIGH QUALITY PORTRAIT LENS

Great for portraits with a medium telephoto perspective, The RF 135mm f/1.8L IS USM allows you to take full advantage of the large f/1.8 aperture, with an extremely shallow depth of field for beautiful background blur.



STEADY SHOTS HAND-HELD OR IN LOW LIGHT

Shoot with confidence even when light levels drop.

The RF 135mm f/1.8L IS USM has 5.5 stop Image Stabilization and in conjunction with selected EOS R series camera, can achieve up to 8.0 stops coordinated control IS. Shoot handheld in dim light or while using slower shutter speeds without the need of a tripod.



FAST AND SMOOTH AUTOFOCUS

The RF 135mm f/1.8L IS USM is equipped with a high-speed and quiet Nano USM. Its smooth and accurate auto focus capabilities makes tracking moving subjects easy - especially when capturing videos.



SHOOT INTO THE LIGHT WITH CONFIDENCE

Don't fear the flare. Shoot into the light with Canon's multi-layered Air Sphere Coating (ASC) protecting against flare, ghosting and reduced contrast.



BUILT WITH THE LEGENDARY L SERIES DURABILITY

The RF 135mm f/1.8L IS USM has been carefully crafted with weather-sealing and fluorine coatings to guard against waterdrops and dust, helping keep this powerful lens safeguarded wherever you go.



RF 135mm f/1.8L IS USM | SPECIFICATIONS

RF 135mm f/1.8L IS USM	
Mount	RF
Focal Length	135mm
Maximum Aperture	f/1.8
Minimum Focusing Distance	0.7m
Maximum Magnification	0.26x
Lens Construction	17 elements in 12 groups
Filter Size Diameter	82mm
Aperture Blades	9
Image Stabilization	5.0 stops (when using the EOS R) 8.0 stops (when using the EOS R3)
Focus Drive System	Nano USM
Dimensions	89.2 x 130.3mm
Weight	935g
Lens Hood	ET-88B (included)
Lens Cap	E-82II (included)
Lens Pouch	LP1319 (included)



www.canon.com.au www.canon.co.nz