



Scandinavian Design

Vintec products are designed in Denmark and Sweden. Our wine cabinets are designed to protect your wines against all external influences, while allowing them to mature under optimal conditions.

50 bottle* dual zone cellaring & serving wine cabinet. *based on a Bordeaux shaped bottle

Product Benefits & Features

Stable Temperature

Our wine cabinets maintain a stable temperature to keep your wine in perfect cellaring conditions. This is thanks to the Triple Glazed, UV treated, insulated side panels and interactions between a compressor and thermostat.

- Visual alert
- Humidity recycling system
- LED digital display panel
- Security lock
- Energy Efficient R600a Gas
- Winter function for cold climates



Humidity above 50%

Our wine cabinets incorporate a Thermal Recycling Pump that ensures adequate humidity levels are maintained. The Thermal Recycling Pump works by heating condensed water, which is then introduced as humid air within the cabinet.



UV Protected Dark Storage Area

UV rays negatively impact the quality of your wine. Our cabinets eliminate this threat by incorporating UV treated tinted glass doors or solid doors, dark interiors and dimmed internal LED lights.



Vibration Reduction System

To protect the storage life and quality of your wine, our cabinets have been designed to create a vibration proof environment by including an externally housed compressor, rubber shock absorbers and vibration absorbing wooden shelves.

Quality Air Flow

Our cabinets include internal and external fans to ensure there is a slow reticulated air flow throughout the cabinet


Product Specification

Type	Wine Cabinet	Fridge door opening	Reversible
RangeName	Noir	Door Type	Glass Door
Function	Cellar OR Serve	Door Construction	Triple Glazed, UV treated
Main Function	Serve Red or White	BodyFinish	Black
Alternate Function	Serve or Cellar	Finish	Borderless Black Glass
ZonesDenomination	Dual-Zone	Hinge	Right
No of Zones	2	Reversible	Yes by customer; charges apply for service
Temperature Range Zone 1 (deg)	6 - 12	Product Installation	Built-In or Freestanding
Temperature Range Zone 2 (deg)	12 - 18	Installation Type	Slot-in
UVTreated	Yes	Height (mm)	820
Lock	Yes	Width (mm)	595
Alarm	Visual	Depth (mm)	563
Display Panel	LED Digital Display	Depth Door Open (mm)	1140
Internal Heater	Yes	Joinery cut out dimension- minimum h	850
Easy Capacity (Bottles)	40	Joinery cut out dimension- minimum w	615
Max Capacity (Bottles)	50	Joinery cut out dimension- minimum d	600
Number of Shelves	4	Air space above cabinet (mm)	30
Shelving Material	Wood	Air space at sides (mm)	20
Shelving Type	3 Full, 1 Half	Rear Spacer (mm)	30
AdjustableShelves	Yes	Ambient Temperature (deg)	16-43
SlidingShelvesType	Standard glide rails, partial extension	Weight Loaded	102
Lighting	White LED		
LightPosition	Top		
Handle	Recessed		

VINTEC

Dimension and Installation Guide

VW40SG2EBK (V40SG2EBK)



© 2018 Vintec Inc. All rights reserved. Vintec Inc. is a registered trademark of Vintec Inc.

vintec.com