



HYDROTAP G5 CHA CELSIUS ARC BRUSHED CHROME



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H58788Z01AU

Zip HydroTap Design Range CELSIUS Chilled Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Manufacturing Code H58788Z01AU

Capacity Residential



Tap Zip HydroTap Design Range CELSIUS ARC Tap (Brushed Chrome)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold and Hot

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 0.17kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D406mm x H333mm

Product Approvals WaterMark, RCM, ARC

Wels Rating 5 Star, 5.5 litres

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

200
333
50
Command Centre width

Air outlet louvre (if required)
Cut-out in door/wall, towards the top of the cabinet
285 80

Air inlet cut-out (required)
Cut-out in cabinet floor
max. 43 326

HydroTap Tap options

Celsius Arc Tap

220 422 138 255 154 23 49 54 71 88 33 45° 45°

Celsius Cube Tap

220 352 138 255 154 23 49 54 71 88 33 45° 45°

Mains hot water supply installation

Hot and cold water supply required

35mm hole in sink/benchtop for mixer tap
RED marked braided hose to mixer tap
Hot water isolation valve (not supplied)
BLUE marked braided hose
Braided hose to HydroTap Command Centre MAINS inlet
Mains water isolation valve (not supplied)

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.

Ø35mm hole for Tap

422
4mm buffer pad air space
Sink
Celsius Arc Tap
Clearance Envelope

200 min.
333
50 min. 280 50 min.
Mains cold water isolation valve (not supplied)
Air inlet grille IEC Flex & Plug 230-240V, 50Hz power outlet
406

HydroTap G5 C Home

shown with Celsius Arc Tap

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

