



HYDROTAP G5 BCS ELITE PLUS CHROME



BOILING



CHILLED



SPARKLING

FILTERED

Order Code H5E783Z00AU

Zip HydroTap Design Range Boiling, Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code	H5E783Z00AU
--------------------	-------------

Capacity	Residential
----------	-------------

Tap	Zip HydroTap Design Range ELITE PLUS Tap (Chrome)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.53kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W339mm x D460mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

BKL2 HydroTap G5 v1.00 02.21 BCS BCS20

Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small>		HydroTap Tap options	Font options	
Clearance envelope Position the Tap and the Command Centre as close together as possible.		Classic Plus Elite Plus	Raised Font with 135mm Extension	Font with 135mm Extension
<p>Air outlet louvre (if required) Cut-out in door/wall, towards the top of the cabinet</p> <p>285 x 60</p>	<p>Air inlet cut-out (required) Cut-out in cabinet floor</p> <p>max. 43 x 326</p>	Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory). 35mm hole for HydroTap Tap 	Cutting detail Raised Font 10 for M6 stud, 86 hole for bowl, 35 hole for tap, 116 width, 152 depth, 164 mounting hole offset.	Cutting detail Standard Font 108 hole for bowl, 35 hole for tap, 116 width, 104 depth, 219 mounting hole offset.
<p>SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.</p>				

**HydroTap G5
BCS Home**

shown with "Classic Plus" Tap

