



# Evolution® 200

## Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

## Features

- Evolution ultra-quiet technology
- Evolution 3-stage grind technology
- Auto-reverse grinding action
- High-torque Dura-Drive™ induction motor
- Built-in air switch with chrome button
- 6 Year guarantee
- Stainless steel grind elements and grind chamber
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation




#### Batch feed operation



For those who prefer the on/off switch built right into the disposer cover, InSinkErator offers the cover control accessory. It's just right for efficient batch feed operation. (Not available in all markets)

#### Dimensions (cm)



Evolu	volution 200				
Α	33.0	D	23.4		
В	18.5	Ε	16.8		
С	6.4				

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

## Sample Specification

Food waste disposer(s) shall be InSinkErator® Model Evolution 200 with 3-stage grind and ultra-quiet technologies, 1 hp (110-120V) or .75 hp (220-240V) motor, auto-reverse grind system, stainless steel grind chamber, grinding elements and built-in air switch in chrome.

Guarantee: 6 Year parts and service.

The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

### **Specifications**

Type of Feed	Continuous	
On/Off Control	Wall Switch or Built-In Air Switch	
Motor	Single Phase	
Reversing	Auto-Reverse Grind System	
Time Rating	Intermittent	
Lubrication	Permanently Lubricated Upper & Lower Bearings	
Shipping Weight (Approx.)	11.4 kg	
Unit Finish	Stainless Steel Light Gray	
Overall Height	33.0 cm	
Grind Technology	3-Stage Grind Technology	
	Jam Preventing Circuit	

Sound Technology  Anti-Vibration Mour and Tailpipe Quiet Sink Baffle Multi-Layer Sound Insulation Premium Stainless	ting
Multi-Layer Sound Insulation	
Insulation	
Premium Stainless	
Steel Stopper	
Grind Chamber 1180 ml Capacity	
Motor Protection Manual Reset Overl	oad
Average Water Usage Approximately 4.0 per Person per Day	
Average Electrical 3-4 KWH per Annul Usage	n
Drain Connection 1-1/2" (3.81 cm) Anti-Vibration (Hose Clamp)	
Dishwasher Drain Yes Connection	

Volts/Hz	HP	Average Load
120V, 60 Hz	1.0	10.2 A
220-240V, 50-60 Hz	.75 (@240V/50Hz)	370 W



InSinkErator Division